

VARIOUS HARLEY-DAVIDSON® APPLICATIONS H.T. STEEL DOWELS



Application

- S&S “Oversized” Dowel for 4” to 4-3/8” Cylinder Dowel
- Oversized Cone Dowel for 1948-’05 Various HD® Applications

KPMI® H.T. Steel Dowel is the Choice of Champions

- Heat Treated Steel
- Black Oxide Coated for Corrosion Resistance
- See Description Below for Special Design Features

This KPMI® dowel has been designed to replace the S&S .250” cylinder dowel, or to be used as desired. This dowel features a unique witness line in the center of the part which serves two purposes. First, this witness line serves as a marker for proper installation height and, second, to create two distinct halves of the part. One end of the dowel has a .252” diameter with a machined dimple on the end so you know to use that end in the case or cylinder. The other half incorporates a .250” diameter. This purpose-made change in diameter, and interference, ensures a snug fit on one end and a slip fit on the other as well as fret free use.

Dowels • Cone • Oversize • H.T. Steel

Material	OD 1	OD 2 O/S	OL	O/S-Rep. HD® P/N	O/S-Rep. S&S P/N
H.T. Steel	0.250”	0.252”	0.520”	366	50-8022



KPMI P/N	Quantity
83240-4	Pkg. of 4
83240-8	Pkg. of 8
83240-20	Pkg. of 20

Retail Price List

KPMI P/N	Description	Retail	Qty. Incentive
83240-4	Dowels • Cone • Oversize • H.T. Steel (Pkg. of 4)	\$8.33	0%
83240-8	Dowels • Cone • Oversize • H.T. Steel (Pkg. of 8)	\$16.65	0%
83240-20	Dowels • Cone • Oversize • H.T. Steel (Pkg. of 20)	\$39.55	5%

Manufacturing Valvetrain For 80 - Years & 2 - Generations

VISIT US AT WWW.KPMI.US