YAMAHA° YZ" 250F 2014-'18 / WR" 250F & YZ" 250FX 2014-'19



October 27, 2025

Valve Spring Kit • Lightweight Racing for Titanium Valves



KPMI P/N	Туре	Max	Valve Lift	Installed Heig		ht	Seat Pressure	Open Pressure		@ Lift
80-80900	Intake	.425"		1.180"		48#	151#		.425"	
80-80900	Exhaust		.400"	1.125"			40#	119#		.400"
		2	In Titanium	Retainers 2 In		In	In CrSi Valve Springs		In H. T. Stee	el Basewashers
Kit Includ	ies	2	Ex Titanium	2	Ex CrSi Valve Springs		Ex CrSi Valve Springs 2 Ex H. T. Ste		el Basewashers	

Valve Spring Kit • Lightweight Racing for Stainless Valves



KPMI P/N	Туре	Max	x Valve Lift	Installed Height		ht	Seat Pressure	Open Pressure		@ Lift
80-81400	Intake		.395"	1.150"		55#		151#	.395"	
00-01400	Exhaust		.370"	1.100"			46#		119#	.370"
		2	In Titanium	Retainers 2 In		In	CrSi Valve Springs	2	In H. T. Stee	l Basewashers
Kit Includ	ies	2	Ex Titanium	Retainers 2 Ex CrSi Valve Springs 2 Ex H. T. Ste		Ex CrSi Valve Springs		el Basewashers		

Intake Only • Titanium Valve Kit



KPMI P/N	Type	*Max Val	ve Lift	Installed Height	Sea	t Pressure	Open Pressure	@ Lift
80-80970	Intake	.425	<u>.</u>	1.180"		48#	151#	.425"
Kit Includ	daa	2	Inta	ke Titanium Retaine	rs	2	Intake CrSi Valv	e Springs
Kit includ	ies	2	Intake	H. T. Steel Basewas	hers	2	Intake Tensilite® Tita	anium Valves

^{*} It may be necessary to use KPMI shortened valve guides (KPMI® #80-8092X & 80-8093X) to achieve higher than stock lift.

Top End Service Kit For WR / YZ 250F 2014-2016



	KPMI P/N	Piston Bore Size	Type		Max Valve Lift		Installed Height		Seat Pressure			Open ressure	@ Lift
	80-81200 77.00mm		Intake		.395"		1.150"		55#		151#		.395"
	00-01200	77.00111111	Exhaust		.370"		1.100"		46#		119#		.370"
			2	2 In Titanium Retair			2	In	CrSi Val	e Springs	2	In H. T. Stee	l Basewashers
	Vit Inclu	doo	2	Ex Ti	tanium Retair	ners	2	Ex	Ex CrSi Valve Springs			Ex H. T. Stee	el Basewashers
	Kit Includes		2	In	Black Diamo	ond [™]	™ Valve	es	2	Ex Black Diamond [™] Valves			Valves
			1	Н	ligh Performan	ice F	Piston Ki	t	1	Top End Gasket Kit			

IMPORTANT NOTE: The piston <u>assembly</u> (piston, rings, valves, pin and pin clips) in this kit are designed to work together as a system. When used complete, the piston <u>assembly</u> can be used as an OEM replacement. The individual components are **NOT INTERCHANGEABLE with O.E.M. valves and piston assembly components.**

Components · Replacement · Top End Service Kit For WR / YZ 250F 2014-2016

KPMI P/N	Description	Specification
80-81400	Spring Kit	Includes: Ti Retainers, CrSi Valve Springs, H.T. Steel Basewashers
80-80912	Intake, Standard Valve	Valves • Black Diamond™ • Black Nitroneg Stems
80-80916	Exhaust, Standard Valve	Valves • Black Diamond™ • Black Nitroneg Stems
80-81201	Gasket Kit	Includes: Head Gasket 77mm Bore (1), Base Gasket (1), Exhaust Gasket (1), Cam Chain Tensioner Gasket (1), Ex. Valve Stem Seal (2), In. Valve Stem Seal (2), Cylinder Head Drain Seal (1), Cam Chain Tens. Crush Seal (1), TPS O-ring (1)

These components are intended for use with the KPMI® Top End Kit and are not intended for OEM compatibility.



YAMAHA° YZ" 250F 2014-'18 / WR" 250F & YZ" 250FX 2014-'19

October 27, 2025

Cylinder Head Service Kit






KPMI P/N	Type	M	ax Valve Lift Installed Height Seat Pressure Open Pressure				@ Lift					
80-82410	Intake	.395"		1.150"		,		55#	151#		.395"	
00-02410	Exhaust	.370"		1.100"			46#	119#		.370"		
		2	In Titanium Re	etainers	2	In Cr	Si Val	ve Springs	2	In H. T. Steel Basewashe		
		2	Ex Titanium R	etainers	iners 2 Ex CrSi Va			ve Springs	2	Ex H. T. Steel	Basewashers	
Kit Includ	es	2	In Std. Black	Diamon	Diamond [™] Valves			Ex Std.	Std. Black Diamond™ Valves			
		2	In Std. C674 Valves Guides					Ex Std. C674 Valves Guides				
		1				То	p End	Gasket Kit				

Components • Replacement • Cylinder Head Service Kit



KPMI P/N	Description	Specification
80-81400	Spring Kit	Includes: Ti Retainers, CrSi Valve Springs, H.T. Steel Basewashers
80-80912	Intake, Standard Valve	Valve • Black Diamond™ • Black Nitroneg Stems
80-80916	Exhaust, Standard Valve	Valve • Black Diamond™ • Black Nitroneg Stems
80-80920	Intake, Standard Valve Guide	Valve Guide • C674 Bronze
80-80930	Exhaust, Standard Valve Guide	Valve Guide • C674 Bronze
80-82411	Gasket Kit	Includes: Head Gasket 77mm Bore (1), Base Gasket (1), Exhaust Gasket (1), Cam Chain Tensioner Gasket (1), Ex. Valve Stem Seal (2), In. Valve Stem Seal (2), Cylinder Head Drain Seal (1), Cam Chain Tens. Crush Seal (1), TPS O-ring (1)

Valves • O.E.M. Replacement • Tensilite® • Chromium Nitride PVD Coated Titanium



KPMI P/N	Туре	Head Dia	ameter	Stem Diameter		0. L.	Material	Rep. OEM P/N
80-80912T	Intake	ake 31.00mm 1.220"		0.1962"	18° 3.280"		Titanium	1SM-12111-10-00
80-80916T	Exhaust	25.00mm	0.984"	0.1760'	30°	3.235"	Titanium	1SM-12121-10-00


Note: These valves are intended as O.E.M. replacement valves and are completely compatible with the O.E.M. spring kits. However, experienced engine builders, who are running aggressive camshafts or higher than factory RPM's may find the combination of the O.E.M. Style Valve and KPMI's Lightweight Racing Spring Kits advisable. All titanium valves are (Tensilite®) PVD CrN coated, and all stainless valves are Black Diamond™ coated.

Valves • Black Diamond™ • Black Nitroneg Stems



KPMI P/N	Туре	Head Dia	meter	Stem Diameter	Tulip	0. L.	Remarks
80-80912	Intake	31.00mm	1220"	0.1962"	18°	3.265"	Standard
80-80916	Exhaust	25.00mm	0.984"	0.1760"	30°	3.235"	Standard

Valve Guides • C674 Bronze



YAMAHA° YZ" 250F 2014-'18 / WR" 250F & YZ" 250FX 2014-'19



October 27, 2025

Valve Guide Seal Kits · High Performance

D		Intake Stem	O.L	Seal	Seal	Designed for these guide specs					
QA QA		Diameter		O.D.	Style		A	В		С	D
		5.0mm	0.350"	0.405"	4	0.340'	±0.005"	0.303"		0.125"	0.230"
		Exhaust Stem	O.L	Seal	Seal	Designed for these guide specs					
		Diameter	U.L	O.D.	Style		A	В		С	D
ØB —		4.5mm	0.331"	0.370"	4	0.321	±0.002"	0.281"		0.120"	0.240"
Part Nu	80-809	90	Kit In	cludes	2	Intake Vi	ton® Seals	2	Exhaust \	/iton® Seals	

Retail Price List

KPMI P/N	Description	Retail
80-80900	Valve Spring Kit ∙ Lightweight Racing for Titanium Valves	\$220.26
80-81400	Valve Spring Kit • Lightweight Racing for Stainless Valves	\$220.26
80-80970	Intake Only • Titanium Valve Kit .425" Lift	\$261.51
80-81200	Top End Service Kit For WR / YZ 250F 2014-2016	\$732.91
80-81201	Gasket Kit For WR / YZ 250F 2014-2016	\$60.99
80-82410	Cylinder Head Service Kit	\$398.61
80-82411	Gasket Kit	\$60.99
80-80912T	Valve (OEM Replacement), Ti. Intake, Std.	\$92.51
80-80916T	Valve (OEM Replacement), Ti. Exhaust, Std.	\$92.51
80-80912	Valve, Black Diamond™ , Intake, Std.	\$31.01
80-80916	Valve, Black Diamond™ , Exhaust, Std.	\$31.01
80-80920	Guide, C630, IN Std.	\$15.92
80-80929	Guide, C630, IN +0.010	\$15.92
80-80930	Guide, C630, EX STD	\$15.92
80-80939	Guide, C630, EX +0.010	\$15.92
80-80990	Seal Kit, Red Viton, Intake/ Exhaust	\$13.96

Contact a KPMI® Sales Representative Todayi

650-557-2046, Ext. 802